

LK-D30

POS PRINTER

Advanced Dot Impact Printer



PRINTING	METHOD	9-pin Serial Dot Impact Matrix
	SPEED	5 Lines/sec
	RESOLUTION	160DPI / 80DPI
	WIDTH	63.5mm (2.5inch)
	NO. OF COLUMNS	TM-U200 Emulation : 42/35, 40/33 Other Emulation : 40/33
	NO. OF TOTAL DOTS	400 Dots/Line
	FONT SIZE	7 x 9, 9 x 9 / 5 x 9, 7 x 9
	LINE SPACING	n/144 inch
	DIRECTION	Bi-Directional (with Logical Seeking)
	INK RIBBON	ERC-38 Compatible (Black, Purple, Black/Red)
PAPER	MEDIA	Roll Paper
	WIDTH	57.5, 69.5, 76.2 mm
	DIAMETER	Max 80 mm (3.0 inch)
	COPIES	Original + 2 Copies
DATA BUFFER	48 Kbyte	
CASH DRAWER DRIVER	2 circuits(24V, 1A max)	
SENSOR	Paper End Sensor, Paper Low Sensor, Cover Open Sensor, Black Mark Sensor(Optional)	
INTERFACE	Serial(RS-232C), Parallel(Centronics 36pin), USB, Combo(Serial+USB), Ethernet, Wi-Fi(802.11b)	
EMULATIONS	TM-U200, TM-U300, iDP-3540, SP200 Command Compatible	
DRIVER	Windows Printer Driver(7, XP, 2000, 2003, Vista, 32 & 64 bit, XP Embedded), Linux, OPOS, WEPOS, JavaPOS	
POWER SUPPLY	TYPE	External SMPS
	INPUT	100 ~ 240Vac 50/60Hz
	OUTPUT	24Vdc / 2.5A
OPERATING CONDITION	5°C ~ 40°C, 10% ~ 80% RH	
STORAGE CONDITION	-20°C ~ 60°C, 5% ~ 95% RH	
RELIABILITY	MCBF	18,000,000 lines
	PRINTHEAD	120,000,000 characters
AUTO CUTTER	TYPE	Guillotine
	LIFE	1,000,000 cuts
	PAPER THICKNESS	0.065~0.13 mm
	CUTTING METHOD	Full / Partial Cut
DIMENSION	W x D x H (mm)	156 x 243.2 x 150.1(mm)
	W x D x H (inch)	6.14 x 9.57 x 5.91(inch)
WEIGHT	CUTTER	2.38 kg
	NON-CUTTER	2.25 kg
CERTIFICATION	FCC, KCC, UL/cUL, CE	
COLOR TYPE	Cool Grey, Ivory	